



## TL TURBO HD DIESEL OIL

**DIESEL ENGINE OIL** : COMMERCIAL VEHICLES.

**SAE GRADE** : 15W-40, 20W-40, 20W-50

**PERFORMANCE LEVEL** : API CF-4

These oils are superior quality diesel engine oil blended from high quality base oil, superior quality of high shares stability viscosity index and specific additives to protect heavy load vehicles, these oils provide excellent oxidation and wear protection, this oil provide excellent lubrication the unique detergent – dispersant inhibitor used in these oil helps in keeping the engine clean, preventing, premature oil thickening.

**Application:** it is Recommended for new generation diesel engine vehicles, these oils can also recommended for on – highway and off highway equipments.

Sr. No	Grade	TL Turbo HD Diesel oil 15W-40	TL Turbo HD Diesel oil 20W-40	TL Turbo HD Diesel oil 20W-50
1	KV.cst @40°C	116	120	140
2	KV.cst @100°C	14 to 15.5	14 to 16	17 to 19
3	VI	135	110	110
4	Flash Point ,°c	210	210	210
5	Pour Point ,°c	-21	-21	-21
6	Density	0.87 to 0.89	0.87 to 0.89	0.87 to 0.89
7	TBN	9 to 11	9 to 10	9 to 10

**Note:** The Above mentioned data are typical and it may vary with batch to batch within permissible specification limits.