



## TL SYNTH 4T

**PETROL ENGINE OIL** : TWO WHEELER VEHICLES.

**SAE GRADE** : 10W-30,

**PERFORMANCE LEVEL** : API SN, JASO MA2

TL SYNTH 4T is blended from semi synthetic base oil and synergistic additives system for outstanding dispersancy characteristic, detergency, anti wear and antioxidant properties, this oil also optimized wet clutch performance, this oil also handle the high stress found in competition engines and minimizes frictional losses and enhance oil life and longer drain period.

**Application** :- TL SYNTH 4T is recommended for high performance 4T motor cycles and scooters, the performance technology has been proven to be compatible with all wet clutch systems.

Sr.No	Grade	TL SYNTH 4T 10W-30
1	KV.cst @100°C	11
2	Density	0.875
3	VI	150
4	Flash Point ,°C	210
5	Pour Point ,°C	-27
6	TBN	7.5
7	Sulphated Ash % wt	0.85

**Note:** The Above mentioned data are typical and it may vary with batch to batch within permissible specification limits.

**Works:** Survey # 13/7A, 14/3, 15/6, Takai Adoshi Rd  
Behind Prasol Chemicals Ltd, Village Honad,  
Post Sajaon, Tal. Khalapur, Dist. Raigad,  
Maharashtra 410203 India

**Web & Email:**  
W: [www.tribolubes.com](http://www.tribolubes.com)  
E: [tpl@tribolubes.com](mailto:tpl@tribolubes.com)  
E: [info@tribolubes.com](mailto:info@tribolubes.com)

**Regd. Office:** 11/102, Bldg. 11, Motilal Nehru Nagar C.H.S.,  
Bandra Kurla Complex, Bandra (E),  
Mumbai, Maharashtra 400051 India  
Tel. +91-22-32278878