


**INDUSTRIAL GEAR OILS:**
**TL AUTO GEAR OILS**

**Performance Level** : EP & HEAVY DUTY TYPE

**SAE GRADE** : 90, 140, 80W-90, 85W-140 & 80W

These oils are superior quality multi purpose extreme pressure gear oils. These oils are used in gear boxes requiring EP properties particularly for hypoid and bevel gears.

Application: Recommended for gear boxes of all types of vehicles requiring EP type of oils. Also can be used in rear axle wheel original equipment manufacturer recommends these types of oils.

| Sr. No. | Characteristics         | Perform. level | K.V. cSt @100°C | VI  | Flash Point, °C | Pour Point, °C | Copper corrosion test |
|---------|-------------------------|----------------|-----------------|-----|-----------------|----------------|-----------------------|
| 1       | TL AUTO GEAR 90 EP      | API GL-4       | 16.9            | 95  | 200             | -9             | 2                     |
| 2       | TL AUTO GEAR 140 EP     | API GL-4       | 28              | 95  | 220             | -6             | 2                     |
| 3       | TL AUTO GEAR 80W-90 EP  | API GL-4       | 14              | 100 | 200             | -24            | 2                     |
| 4       | TL AUTO GEAR 85W-140 EP | API GL-4       | 27              | 98  | 220             | -15            | 2                     |
| 5       | TL AUTO GEAR 80W EP     | API GL-4       | 9.2             | 100 | 200             | -27            | 2                     |
| 6       | TL AUTO GEAR 90 HD      | API GL-5       | 16.9            | 95  | 200             | -9             | 2                     |
| 7       | TL AUTO GEAR 140 HD     | API GL-5       | 28              | 95  | 220             | -6             | 2                     |
| 8       | TL AUTO GEAR 80W-90 HD  | API GL-5       | 14              | 100 | 200             | -24            | 2                     |
| 9       | TL AUTO GEAR 85W-140 HD | API GL-5       | 27              | 98  | 220             | -15            | 2                     |
| 10      | TL AUTO GEAR 80W HD     | API GL-5       | 9.2             | 100 | 200             | -27            | 2                     |

**Note:** The above mentioned data are typical and it may vary with batch to batch within Permissible specification limits.