



TL PREMIUM HDD ENGINE OIL

DIESEL ENGINE OIL : COMMERCIAL VEHICLES

SAE GRADE : 15W-40

PERFORMANCE LEVEL : API CI-4 Plus

TL PREMIUM HD diesel engine oil is developed for LCV / HCVs with or without EGR for BS III / IV vehicles. It meets API CI 4 Plus, ACEA E7, MB 228.3, VDS-3, CES 20076/CES 20077/CES 20078 specs. It has potential for increasing the drain period compares to an API CH-4 OIL. It is recommended for Light or heavy duty trucks, buses, cars and any vehicle fitted with exhaust gas recirculation technology and generating high soot to meet BS II, III & IV emission norms.

| Sr. No | Grade | TL PREMIUM HD DIESEL OIL 15W-40 |
|--------|-----------------|------------------------------------|
| 1 | KV.cst @40°C | 120 |
| 2 | KV.cst @100°C | 14 to 15.5 |
| 3 | VI | 140 |
| 4 | Flash Point ,°C | 210 |
| 5 | Pour Point ,°C | -21 |
| 6 | Density | 0.87 to 0.89 |
| 7 | TBN | 9 to 11 |

Note: The Above mentioned data are typical and it may vary with batch to batch within permissible specification limits.