



## TL TURBO HDD ENGINE OIL

**DIESEL ENGINE OIL** : COMMERCIAL VEHICLES.

**SAE GRADE** : 15W-40, 20W-40, 20W-50

**PERFORMANCE LEVEL** : API CF-4

TL TURBO HD diesel engine oils are specially designed for heavy duty commercial vehicles with turbo charged engines. It meets API CF4. It provides excellent engine cleanliness and protection against wear and corrosion.

**Application :-** TL TURBO HD diesel engine oils is recommended for use as crankcase oils for slow, medium and high speed stationary diesel engines, e.g. Generator Set Oil etc. It is suitable for all reasons and reduces oil consumptions.

Sr. No	Grade	TL TURBO HD DIESEL OIL 15W-40	TL TURBO HD DIESEL OIL 20W-40	TL TURBO HD DIESEL OIL 20W-50
1	KV.cst @40°C	116	120	140
2	KV.cst @100°C	14 to 15.5	14 to 16	17 to 19
3	VI	135	110	110
4	Flash Point ,°C	210	210	210
5	Pour Point ,°C	-21	-21	-21
6	Density	0.87 to 0.89	0.87 to 0.89	0.87 to 0.89
7	TBN	9 to 11	9 to 10	9 to 10

**Note:** The Above mentioned data are typical and it may vary with batch to batch within permissible specification limits.